

Facsimile

ROBERT H. HAMMER III, P.C.
Attorney at Law
3121 Springbank Lane
Suite I
Charlotte, North Carolina 28226, U.S.A.
Tel.: (704) 927-0400
Fax: (704) 927-0485
bhammer@hammerpatent.com

To: Examiner I. Borissov
703 746 8493

Date: May 17, 2004

From: Robert H. Hammer III

Total Pages: 5

Re: Appln Serial No. 09/821,553
Unofficial Amendment for discussion during telephonic interview
5512.001

Dear Sir:

Per your request, attached are unofficial amended claims for review during the interview scheduled for Wednesday, May 19th at 1:00 EST. I will be joined by the inventor, Bob Spotnitz.

We would like to explain how the instant amendment distinguishes the Notten reference. Please note Notten, Figures 1 and 2. Input is received, in Fig 1, from the battery 110 (col 7, lines 50-55) and in Fig 2, from battery terminals connected at 202, 203 (col 9, lines 45-50). This device does not receive input from a customer.

We will call you on Wednesday.

Thank you,



Bob Hammer

Cc: B Spotnitz – fax 925 600-9812
H:\5512\1\Borissov051704.doc

The information contained in this facsimile may be confidential, and is intended only for the use of the individual(s) or entity(ies) named above. If the reader of this message is not the intended recipient, please be advised that any use, dissemination, or duplication of this communication is strictly prohibited. If this communication has been received in error, please contact the sender (call collect) and we will arrange to reimburse you for the return of this facsimile to us by return mail. Thank you for your cooperation.

SN 09/821,553

5512.001

RHH 5/17/04

1. (Currently amended) A method for customer driven charge storage device design comprising the steps of:

providing more than one model of a charge storage device, the model adapted to convert at least one customer input into at least one output;

providing an interface, the interface being adapted to pass input to the model, the interface being adapted to pass output from the model, and the interface being adapted to hide the model;

wherein the customer addresses the interface with the input, the interface directs the input to at least one of the models, the model generates the output that passes through the interface to the customer.

1. (Original) The method of claim 1 wherein the model is selected from the group consisting of first principles' models, empirically-based models, and hybrid models consisting of combinations of first principles' models and empirically-based models.

2. (Original) The method of claim 1 wherein the input further comprised a plurality of inputs.
3. (Original) The method of claim 1 wherein the output further comprises a plurality of outputs.
4. (Original) The method of claim 1 wherein the model further comprises a database, the model and the database being in communication.
5. (Original) The method of claim 1 wherein the output further comprises a design of the charge storage device.
6. (Previously amended) A method for customer-driven charge storage device design comprising the steps of:
 - providing a customer interface adapted for defining customer test procedure for a desired charge storage device and defining customer requirement for the charge storage device;
 - providing a plurality of charge storage device models;
 - providing a routine capable of selecting at least one of the charge storage device models;

executing a simulation wherein the customer test procedure, the customer requirement, and the selected charge storage device model are combined to render a custom charge storage device design and the models are hidden from the customer;

storing the custom charge storage device design;
and

outputting the custom charge storage device design.

7. (Original) The method of claim 7 wherein the selecting routine being adapted for either customer selection of routine selection based upon, at least in part, the customer test procedure and the customer requirement.

8. (Original) The method of claim 7 wherein the model further comprises a sizing program and a performance program.

9. (Original) The method of claim 7 wherein the model further comprises a sizing program and a performance and an abuse program.

10. (Original) The method of claim 7 wherein executing a simulation further comprises the step of optimizing the simulation.

12. (Original) The method of claim 7 wherein outputting the custom charge storage device design further comprises the step of reporting the design.